



Toll Free: 1-888-697-5585

# When performance matters scaffold professionals choose **SURE-LAM™ 2.25E** **LVL Scaffold Plank**

**SURE-LAM™ 2.25E** is manufactured in the USA, using only high quality Douglas Fir veneer.

The superior strength of Douglas Fir combined with a state of the art manufacturing process ensures you will get an LVL scaffold plank that you can depend on.

**QUALITY PRODUCTS. COMPETITIVE PRICING.**

**Call us today for a quote on a partial or full load to your yard or job. 1-888-697-5585**



- Meets OSHA/ANSI Standards
- APA/EWS Independent Third Party Inspection
- ICBO 1997 Uniform Building Code – Structural LVL
- Individually Proof Tested
- Custom Embossing
- Custom Lengths and Sizes



[www.kennisonforest.com](http://www.kennisonforest.com)

SURE-LAM™ 2.25E DF LVL							
Loading Conditions	Simple Span						
	1 1/2" x 9 1/4"	1 1/2" x 9 1/2"	1 1/2" x 11 1/4"	1 3/4" x 9 1/2"	1 3/4" x 11 1/4"	2" x 11 1/4"	2 1/2" x 11 1/4"
50psf	11' - 0"	11' - 0"	11' - 0"	12' - 10"	12' - 10"	14' - 8"	18' - 5"
75 psf	9' - 7"	9' - 7"	9' - 7"	11' - 3"	11' - 3"	12' - 10"	16' - 1"
1 - Person	11' - 4"	11' - 6"	12' - 6"	14' - 6"	15' - 10"	19' - 4"	27' - 0"
2 - Person	8' - 9"	8' - 10"	9' - 6"	10' - 10"	11' - 8"	14' - 1"	19' - 5"
3 - Person	6' - 1"	6' - 3"	7' - 0"	7' - 9"	8' - 9"	10' - 8"	15' - 2"

Loading Conditions	2 - Equal Spans						
	1 1/2" x 9 1/4"	1 1/2" x 9 1/2"	1 1/2" x 11 1/4"	1 3/4" x 9 1/2"	1 3/4" x 11 1/4"	2" x 11 1/4"	2 1/2" x 11 1/4"
50 psf	12' - 4"	12' - 4"	12' - 4"	14' - 5"	14' - 5"	16' - 6"	20' - 8"
75 psf	10' - 10"	10' - 10"	10' - 10"	12' - 7"	12' - 7"	14' - 5"	18' - 0"
1 - Person	13' - 5"	13' - 7"	14' - 9"	17' - 1"	18' - 8"	22' - 9"	31' - 10"
2 - Person	9' - 6"	9' - 7"	10' - 5"	12' - 1"	13' - 2"	16' - 1"	22' - 6"
3- Person	6' - 11"	7' - 1"	8' - 0"	8' - 10"	10' - 1"	12' - 5"	17' - 8"

**Notes:**

1. Spans are from center-to-center of scaffold supports.
  2. The weight of the plank has been included in all calculations, and is included as a "Dead Load".
  3. Deflections are limited to L/60 per OSHA requirements.
  4. The "Person" load is defined in ANSI A10.8 as a person weighing 200 pounds, carrying 50 pounds of equipment.
- The "1-Person" load is applied at mid-span.
  - The "2-Person" load is applied with each "Person" load placed 18" to either side of mid-span.
  - The "3-Person" load is applied with a "Person" load at mid-span, and a "Person" load at 18" to either side of mid-span.

Sold exclusively by Kennison Forest Products, Inc.  
P.O. Box 115 Sulphur, LA 70664  
P: 337-527-5585 F: 337-527-0412  
[www.kennisonforest.com](http://www.kennisonforest.com)

